

IN THE CLAIMS:

Please amend the claims as indicated in the complete listing of pending claims listed below.

1. (Currently Amended) A method, comprising:  
integrating ~~a pseudo-localization process~~ at least one pseudo localization utility application with a build ~~application process~~, ~~wherein the pseudo-localization process includes at least one pseudo localization utility application;~~  
executing the at least one pseudo localization utility application to generate pseudo-translated locale-dependant code, wherein executing the at least one pseudo localization utility application includes:
  - (a) retrieving locale-dependant code from at least one storage location;
  - (b) altering an appearance of the locale-dependant code; and
  - (c) storing the altered locale-dependant code in at least one second storage location; andgenerating a pseudo-language build with the pseudo-translated locale-dependant code.
2. (Original) The method of claim 1, further comprising:  
testing the pseudo-language build; and  
identifying at least one internationalization bug.
3. (Original) The method of claim 2, wherein the internationalization bug comprises a hard-coded string, a hard-coded format, or a hard-coded reference to a translation.

4. (Original) The method of claim 2, wherein identifying the at least one internationalization bug comprises discovering unaltered locale-dependant code in the user-interface.
5. (Original) The method of claim 1, wherein altering the appearance of the locale-dependant code comprises adding at least one prefix character to the locale-dependant code.
6. (Original) The method of claim 5, wherein the at least one prefix character comprises at least one multi-byte character.
7. (Original) The method of claim 5, wherein the at least one prefix character comprises at least one right-to-left character.
8. (Original) The method of claim 5, wherein the at least one prefix character comprises a prefix string including at least one multi-byte character and at least one right-to-left character.
9. (Original) The method of claim 1, wherein the at least one pseudo localization utility application comprises at least one server message specific utility, and the locale-dependant code comprises at least one server message.

10. (Original) The method of claim 1, wherein the at least one pseudo localization utility application comprises at least one repository string specific utility, and the locale-dependant code comprises at least one repository string.
11. (Original) The method of claim 1, wherein the at least one pseudo localization utility application comprises at least one resource file specific utility, and the locale-dependant code comprises at least one resource file.
12. (Original) The method of claim 1, wherein the at least one pseudo localization utility application comprises at least one utility application capable of retrieving or altering at least one element of user-interface code of a type selected from a group, including: a server message, a repository string, a static UI file, and a seed data file.
13. (Currently Amended) The method of claim 1, wherein the build ~~process~~ application comprises a database build-~~process~~ application, the at least one pseudo localization utility application comprises at least one seed data file specific utility, and the locale-dependant code comprises at least one seed data file.
14. (Currently Amended) The method of claim 1, wherein the build ~~process~~ application comprises a software build-~~process~~ application.
15. (Currently Amended) An article of manufacture, comprising:  
a machine-readable medium including instructions stored thereon, which, when  
executed by a machine, cause the machine to:

implement ~~a pseudo localization process~~ at least one pseudo localization utility application integrated with a build ~~process application~~, wherein the pseudo localization process includes at least one pseudo localization utility application;

execute the at least one pseudo localization utility application to generate pseudo-translated locale-dependant code ~~through~~ through

(a) retrieving locale-dependant code from at least one storage ~~location~~;  
location,

(b) altering an appearance of the locale-dependant ~~code~~ code, and

(c) storing the altered locale-dependant code in at least one second storage location; and

generate a pseudo-language build with the pseudo-translated locale-dependant code.

16. (Original) The article of manufacture of claim 1, wherein the machine-readable medium further includes instructions, which, when executed by a machine, cause the machine to:  
  
test the pseudo-language build; and  
  
identify at least one internationalization bug.
17. (Original) The article of manufacture of claim 16, wherein the internationalization bug comprises a hard-coded string, a hard-coded format, or a hard-coded reference to a translation.

18. (Original) The article of manufacture of claim 16, wherein identifying the at least one internationalization bug comprises discovering unaltered locale-dependant code in the user-interface.
19. (Original) The article of manufacture of claim 15, wherein altering the appearance of the locale-dependant code comprises adding at least one prefix character to the locale-dependant code.
20. (Original) The article of manufacture of claim 19, wherein the at least one prefix character comprises at least one multi-byte character.
21. (Original) The article of manufacture of claim 19, wherein the at least one prefix character comprises at least one right-to-left character.
22. (Original) The article of manufacture of claim 19, wherein the at least one prefix character comprises a prefix string including at least one multi-byte character and at least one right-to-left character.
23. (Original) The article of manufacture of claim 15, wherein the at least one pseudo localization utility application comprises at least one server message specific utility, and the locale-dependant code comprises at least one server message.

24. (Original) The article of manufacture of claim 15, wherein the at least one pseudo localization utility application comprises at least one repository string specific utility, and the locale-dependant code comprises at least one repository string.
25. (Original) The article of manufacture of claim 15, wherein the at least one pseudo localization utility application comprises at least one resource file specific utility, and the locale-dependant code comprises at least one resource file.
26. (Original) The article of manufacture of claim 15, wherein the at least one pseudo localization utility application comprises at least one utility application capable of retrieving or altering at least one element of user-interface code of a type selected from a group, including: a server message, a repository string, a static UI file, and a seed data file.
27. (Currently Amended) The article of manufacture of claim 15, wherein the build ~~process-application~~ comprises a database build-~~process~~ application, the at least one pseudo localization utility application comprises at least one seed data file specific utility, and the locale-dependant code comprises at least one seed data file.
28. (Currently Amended) The article of manufacture of claim 15, wherein the build ~~process-application~~ comprises a software build-~~process~~ application.
29. (Original) A system, comprising:  
a computer system having a processor, a memory, and an input/output device;

an executable build application, stored in the memory of the computer system, and configured, when executed by the processor, to generate a language-specific build; and

at least one executable pseudo localization utility application, stored in the memory of the computer system, and integrated with the build application to generate a pseudo-language, language-specific build, the at least one executable pseudo localization utility application configured, when executed by the processor, to retrieve locale-dependant code from at least one storage location, to alter an appearance of the locale-dependant code, and to store the altered locale-dependant code in at least one second storage location.

30. (Original) The system of claim 29, wherein altering the appearance of the locale-dependant code comprises adding at least one prefix character to the locale-dependant code.
31. (Original) The system of claim 30, wherein the at least one prefix character comprises at least one multi-byte character.
32. (Original) The system of claim 30, wherein the at least one prefix character comprises at least one right-to-left character.
33. (Original) The system of claim 30, wherein the at least one prefix character comprises a prefix string including at least one multi-byte character and at least one right-to-left character.

34. (Original) The system of claim 29, wherein the at least one pseudo localization utility application comprises at least one server message specific utility, and the locale-dependant code comprises at least one server message.
35. (Original) The system of claim 29, wherein the at least one pseudo localization utility application comprises at least one repository string specific utility, and the locale-dependant code comprises at least one repository string.
36. (Original) The system of claim 29, wherein the at least one pseudo localization utility application comprises at least one resource file specific utility, and the locale-dependant code comprises at least one resource file.
37. (Original) The system of claim 29, wherein the at least one pseudo localization utility application comprises at least one utility application capable of retrieving or altering at least one element of user-interface code of a type selected from a group, including: a server message, a repository string, a static UI file, and a seed data file.
38. (Currently Amended) The system of claim 29, wherein the build ~~process~~application comprises a database build-~~process~~application, the at least one pseudo localization utility application comprises at least one seed data file specific utility, and the locale-dependant code comprises at least one seed data file.
39. (Currently Amended) The system of claim 29, wherein the build ~~process~~application comprises a software build-~~process~~application.

40. (New) The method of claim 1, wherein said executing the at least one pseudo localization utility application is in response to a determination in the build application to build a pseudo-language build.